

# SK PRIME

## 78M PLATFORM SUPPORT VESSEL 4000 DWT | DP 2 | FIFI 1

### VESSEL PARTICULARS

<b>Class</b>	BV I ✕HULL ✕MACH Supply Vessel ✕AUT-UMS Fire fighting ship 1 - water spraying Oil recovery ship SP60 -flash point > 60°C -oil Product LHNS ✕DYNAPOS AM/AT R Unrestricted navigation INWATER SURVEY
<b>Flag</b>	Malaysia
<b>P.O.R</b>	Port Kelang
<b>Year Built</b>	2016
<b>Builder</b>	Xiamen Shipbuilding Industry
<b>IMO</b>	9727895
<b>O.N.</b>	335645
<b>Call Sign</b>	9MVF6



### DIMENSION

<b>L.O.A.</b>	78.00 m
<b>Beam</b>	18.60 m
<b>Depth</b>	7.80 m
<b>Draft (max)</b>	6.40 m
<b>GRT</b>	3535
<b>NRT</b>	1060

### CARGO CAPACITIES

<b>Deadweight</b>	4151 Tonnes
<b>Deck Cargo</b>	2100 Tonnes
<b>Deck Loading</b>	7.5 Tonnes/m <sup>2</sup>
<b>Deck Area</b>	800 m <sup>2</sup>
<b>Fresh Water</b>	635 m <sup>3</sup>
<b>Drill/Bal Water</b>	1415 m <sup>3</sup>
<b>Fuel Oil</b>	1448 m <sup>3</sup>
<b>Base Oil</b>	218 m <sup>3</sup>
<b>Mud</b>	834 m <sup>3</sup>
<b>Brine</b>	834 m <sup>3</sup>
<b>Methanol</b>	223 m <sup>3</sup>
<b>Dry Bulk</b>	300 m <sup>3</sup>
<b>Recovery oil</b>	1058 m <sup>3</sup>

### ACCOMMODATION

<b>1 Man cabin</b>	8x 1 (8)
<b>2 Men Cabin</b>	4x 2 (8)
<b>4 Men cabin</b>	11x 4 (44)
<b>Total</b>	60 berths
<b>Hospital</b>	1 berth

### PROPULSION & POWER PLANT

<b>Propellers</b>	2x 2206KW Azimuth Thrusters
<b>Bow Thruster</b>	2x 940KW, 14T Thrust each
<b>Main Engine</b>	2x 2206KW 800 rpm
<b>Main Generator</b>	3x 550KW, 440V3Ph60Hz
<b>Shaft Generator</b>	2x 1100KW, 440V3Ph60Hz
<b>Emerg Generator</b>	1x 95KW, 440V3Ph60Hz

### DECK MACHINERY

<b>Tugger winch</b>	2x 10 Tonnes SWL
<b>Capstan</b>	2x 5 Tonnes SWL
<b>Provision Crane</b>	1x 5 Tonnes SWL @ 10 m radius


### CARGO HANDLING CAPACITY

<b>Fresh Water</b>	1x 100 m <sup>3</sup> /hr @ 80 m head
<b>Drill Water</b>	1x 100 m <sup>3</sup> /hr @ 80 m head
<b>Fuel Oil</b>	1x 100 m <sup>3</sup> /hr @ 80 m head
<b>Base Oil</b>	1x 100 m <sup>3</sup> /hr @ 80 m head
<b>Mud</b>	2x 100 m <sup>3</sup> /hr @ 200 m head
<b>Brine</b>	2x 100 m <sup>3</sup> /hr @ 200 m head
<b>Methanol</b>	2x 75 m <sup>3</sup> /hr @ 63 m head
<b>Dry Bulk</b>	2x 25 m <sup>3</sup> /min @ 5.6 bar
<b>Water Maker</b>	1x 15 m <sup>3</sup> /day

### PERFORMANCE

<b>Speed</b>	13.0 knots
--------------	------------

## SK PRIME | 78M PLATFORM SUPPORT VESSEL



THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE SUPPLIED ON THE UNDERSTANDING THAT THEY ARE THE EXCLUSIVE PROPERTY OF FOCAL MARINE & OFFSHORE. THEY MUST NOT BE USED OR REPRODUCED IN WHOLE OR IN PART WITHOUT PERMISSION IN WRITING.

### NAVIGATION EQUIPMENT

Radars, Magnetic Compass, Gyro Compasses, DGPSs, AIS Autopilot, Echo Sounder, Speed Log, Navtex, Weather Fax SSAS, BNWAS, VDR, ECDIS

### COMMUNICATION EQUIPMENT

GMDSS A1+A2+A3, VSAT

### FIRE-FIGHTING EQUIPMENT

**External FiFi** Pump: 2x 1700 m<sup>3</sup>/hr  
 Monitor: 1x 1200 m<sup>3</sup>/hr (water/foam)  
 Monitor: 1x 1200 m<sup>3</sup>/hr (water)  
**Oil Dispersant** 2x 6m spray booms with nozzles

### SAFETY EQUIPMENT

**Rescue Boat** 1x 15 men Fast Rescue Boat  
 118 KW in board engine, waterjet

## SKOM SDN BHD (1182610-K)

B-03-B-17-1, Menara 3A, No.3, Jalan Bangsar, KL Eco City, 59200 Kuala Lumpur, Malaysia

Tel : +603-2280 6777 | Fax: +603-2201 7778 | www.skom.com.my

\*Disclaimer : All information provide here is accurate at the time of printing and may be subjected to change without prior notice. While every reasonable care has been taken in preparing this document, SKOM Sdn Bhd. Will not be held responsible for any inaccuracies.